

**YTONG**



**Product health and  
safety for YTONG  
partition wall panels**



**xella**



# Product health and safety for YTONG partition wall panels

## Authority

Issued under the Health and Safety at Work Act 1974, the Consumer Protection Act 1987 and Control of Substances Hazardous to Health Regulations 2002.

Name of company

Xella BE nv/sa

Kruibeeksesteenweg 24

B-2070 Burcht

Belgium

## Products

YTONG aircrete partition wall panels are hereafter described as 'YTONG panels' unless specifically described otherwise.

## Composition

YTONG panels are manufactured from sand, cement, lime and water.

## Application

YTONG panels are designed and manufactured in various densities, strengths and sizes. They are mainly used in the construction of interior walls, and are usually bonded together with thin joint mortar. YTONG panels must be used strictly in accordance with relevant British or European Standards and Building Regulations.

## Hazards identification

The products, within the meaning of the Health and Safety at Work Act, are inherently safe, but some hazards are identified thus:

- The comparatively sharp edges of YTONG panels require care when handling manually, to avoid risks of cuts or abrasions.
- Wet panels may exhibit alkalinity owing to the cement/lime constituent and care should be taken when handling manually to avoid burns to the skin.
- The panels weight and size should be taken into account when handling, to avoid dropping or strains when lifting. YTONG panels may only be handled with appropriate lifting equipment.
- Silica dust from YTONG panels can be harmful if inhaled or ingested and, as with any dust, may cause irritation to the respiratory and digestive tract.
- Plastic packaging materials are combustible and may constitute a fire hazard.



## First-aid measures

There are no specific requirements when using YTONG panels, other than the treatment of minor injuries. For example, treat dust in the mouth or eye by washing liberally with clean water. Where eye contact occurs, the area must be immediately and thoroughly irrigated using water or a suitable eyewash. Treat dust on the skin by washing liberally with soap and clean water.

In case of doubt, or when symptoms persist, medical advice must be sought.



### Fire-fighting measures

In the event of fire, YTONG panels are not combustible. However, plastic shrinkwrapping, edging strips and timber pallets will burn if ignited. These materials will produce noxious fumes when burnt, and personnel should not be exposed to these. After a fire, packaged YTONG panels may become unstable. They should not be lifted or moved under any circumstances until a competent person has assessed the situation and permission to proceed has been granted.

### Accident release measures

Not applicable.

### Delivery, handling and storage

YTONG panels are generally delivered by road transport and are off-loaded mechanically. When lifted by grab, crane or fork truck, no personnel should be permitted beneath the load. When vehicles are offloading, any overhead power lines or cables should be isolated or otherwise adequately protected.

YTONG panels should always be stacked on a clean, firm, level base to avoid collapse. To prevent the risk of injury from loose panels falling, avoid stacking packs of panels above normal head height unless they are to be handled by mechanical methods.

Ensure suitable stack heights are maintained according to ground conditions – never stack packs more than three high.

Minimise manual handling by delivering units as close to the point of laying as safety considerations permit.

YTONG panels are banded or wrapped, care should be taken when removing the banding to avoid injury from the band under tension, or any loose panels falling when the banding or wrapping is released.

To avoid trips or falls, the work area should be clear of obstructions and properly organised.

### Exposure controls/personal protection

During the processes of cutting, drilling or chasing YTONG panels, there is likely to be exposure to respirable dust. Workplace Exposure Limits should be determined in accordance with EH40, published by the Health and Safety Executive.

The normal protective clothing recommended for wear on building sites, e.g. safety footwear, head protection and gloves, is required. In addition, suitable goggles and dust masks conforming to the appropriate British or European Standard should be worn during the processes of cutting, chasing or drilling.

When working with light - coloured YTONG panels in bright daylight conditions, glare may be experienced and it may be appropriate that suitable eye protection should be worn.

### Physical and chemical properties

YTONG panels are inert when supplied. The main constituents are natural aggregates which contain silica, cement and lime.

### Stability and reactivity

Not applicable.

### Toxicological information

Not applicable.

### Ecological information

Not applicable.

### Transportation information

YTONG panels are not subject to hazardous substance conveyance regulations, and vehicle and package labelling is not required.

### Disposal considerations

All waste materials should be disposed of at a suitable licensed disposal facility, preferably by recycling or re-use. Advice on a preferred method should be obtained from the Environmental Agency (England and Wales) or the Scottish Environment Protection Agency (SEPA).

## **Other information**

Xella's technical staff are on hand to render assistance with written or telephone enquiries.

### **Xella UK**

P.O Box 10028  
Sutton Coldfield  
United Kingdom B75 7ZF  
Tel: +44 (0) 8432 909 080  
Fax: +44 (0) 8432 909 081

E: [silka-uk@xella.com](mailto:silka-uk@xella.com)  
W: [www.xella.co.uk](http://www.xella.co.uk)

### **Xella Nederland BV**

Postbus 23  
4200 AA Gorinchem  
Nederland  
Tel: +31 (0) 183 67 12 34  
Fax: +31 (0) 183 67 12 39

E [verkoop@xella.nl](mailto:verkoop@xella.nl)  
W: [www.xella.nl](http://www.xella.nl)

### **Xella BE nv/sa**

Kruibeeksesteenweg 24  
B-2070 Burcht  
Belgie  
Tel: +32 (0)3 - 250 47 00  
Fax: +32 (0)3 - 250 47 06

E: [ytong-bel@xella.com](mailto:ytong-bel@xella.com)  
w: [www.xella.be](http://www.xella.be)

Disclaimer: Every effort has been made to ensure the correctness of the information provided in this Material Safety Data Sheet which relates to the product described only, and which is supplied to product purchasers on the basis that we cannot guarantee its accuracy or completeness. Health and safety information provided in the Material Safety Data Sheet is intended for general guidance only, and it is the responsibility of the user to ensure that suitable and sufficient assessment of hazards and risks posed in the employment of any products are undertaken and to comply with any duties imposed by Statutory or Regulatory requirements. No statement made in this Material Safety Data Sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe any existing patents, nor is any warranty made, either expressed or implied.